



NUMINOS® DL XL

Indoor LED recessed ceiling light black/white 3000K 20°

From hotels and offices to commercial or private rooms. From application to technology to design in detail: it's good that the modular downlights and spotlights can be configured exactly as required by the design or space in question. The more multifaceted your project is, the more you can benefit from the intelligent NUMINOS® lighting system. Thanks to the wide selection of modules, there is a suitable solution for every need. Combined with the suitable driver, the NUMINOS® lighting family, which can be freely configured and combined, offers over a thousand possibilities. Like the rigid downlight, which, with its light cone directed downwards, is perfect for providing ambient lighting for rooms of various sizes or objects positioned directly below it. With the best workmanship and light quality. You can simply select the desired LED driver (on/off, phase dimming, DALI) for each total wattage via colour coding. This makes easy installation a matter of formality. When will you choose SLV's modular variety? - Here you can find the configurator: www.NUMINOS.SLV.com

TECHNICAL DATA

| | |
|-------------------------------------|----------------------------|
| Item no.: | 1004010 |
| Number of different light outlets | 1 |
| Secondary power / secondary voltage | 1050 mA/V |
| Height | 10.8 cm |
| Diameter | 16.0 cm |
| Installation diameter | 14.5 cm |
| Installation depth | 11.5 cm |
| Net weight | 0.66 kg |
| Gross weight | 0.706 kg |
| IP Code | IP 20 |
| Safety class | III |
| Impact resistance class | IK02 |
| Impact resistance | 0,200000000000000001 Joule |
| Assembly | Recessed |
| Assembly details | Ceiling |
| Wattage | 37.4 W |
| Lumen | 3550 lm |
| Colour temperature | 3000 Kelvin |
| Beam angle | 20 ° |
| Color | black |
| CRI | >90 |
| UGR ? | 18.0000 |

Accessories

| | |
|---------|----------------------------------|
| 1004059 | LED driverm 40W multi mA |
| 1004066 | LED driver , 28-40W 1000mA PHASE |
| 1004071 | LED driver 4.2-50W 1050mA DALI |
| 1004798 | NUMINOS® XL , diffuser Ellipse |
| 1004799 | NUMINOS® XL , diffuser Prisma |
| 1004800 | NUMINOS® XL , diffuser Frosted |
| 1004801 | NUMINOS® XL , diffuser Wabe |

| | |
|-----------------------------|---------|
| Binning | 3 |
| LXXBXX data | 80/50 |
| Service life | 50000 h |
| Minimum ambient temperature | -20 °C |
| Maximum ambient temperature | 40 °C |

Notes
