


2630

Design By Arik Levy

Ceiling light with basic lines and cubic volumes that form sculptures integrated into the architecture.

Model Sheet




Finish	<div style="display: flex; align-items: center;"> <div style="width: 15px; height: 15px; background-color: grey; border-radius: 50%; margin-right: 5px;"></div> <div> <p>15 Grey L2 NCS S 2500-N</p> <p>21 Black Grey NCS S 7000-N</p> </div> </div>
LED temperature color	3000 K / 3500 K / 4000 K
Dimming	DALI / 1-10V / CASAMBI
Installation type	Surface Canopy
Materials	<p>Body: Aluminum</p> <p>Diffuser: Polycarbonate</p> <p>Profile: Aluminum</p>
LED	<div style="display: flex; align-items: center;"> <div style="border: 1px solid black; padding: 2px 5px; margin-right: 5px;">E</div> <div> <p>CRI>90</p> <p>3000 K / 3500 K / 4000 K</p> </div> </div>
Driver	<p>Constant Voltage 110~240 V V</p> <p>50~60 Hz HZ</p>
Remarks	<p>Main input by the biggest box</p> <div style="display: flex; justify-content: space-between; margin-top: 5px;"> Dimmable LED </div> <div style="display: flex; justify-content: space-between; margin-top: 5px;"> IP20 Bi-volt 50-60Hz 1-10V </div>
Application	Ceiling Lamps
Packaging	<p>1 Box</p> <p>0.21 m x 0.31 m x 0.31 m</p> <p>Gross weighth 2.7</p> <p>Net weighth 2.2</p> <p>Vol. 0.0201</p>

Lighting effect

General Lighting


Lamp for general lighting with an opaque shade and distributing light upwards and/or downwards mainly.



Photometric Data

Efficiency	51.19 lm/W
Coordinate System	CG
Total Flux	565.65 lm
Maximum Value	270.71 cd

Other Applications



All of our products come with a five-year warranty. Check our legal terms at www.vibia.com/warranty

Vibia Lighting, S.L.U.

Office / Oficina
Progrés 4-6. 08850 Gavà. Barcelona, Spain.

International T +34 934 796 971
Spain / Portugal T +34 934 796 970

customer.service@vibia.com
vibia.com