

FLOS

03.6055.B1 White/Gold

Kap 80 Surface Square Optic Flood

Designed by FLOS Architectural, 2017




LED - LED array - 9.2W - 732lm - 3000K - CRI> 90 - Beam° 53

Luminaire for mounting on the ceiling with LED light source. Power source incorporated into luminaire body. Non dimmable 110/240V.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



Main specifications

Mounting	Ceiling surface
Environments	Indoor dry location
LED type	LED array
Lamp category	LED
Iicos	No
Number of heads	1
Power (W)	9.2
Source flux (lm)	956
System flux (lm)	732

Physical

Colour	White/Gold
Trim	No
Orientation	Fixed
Net weight (kg)	0.45
IP internal	20
IP external	20

Download

Mounting instructions [↓ PDF](#)

Photometric Files

LDT / IES [↓ ZIP](#)


Technical Drawings

2D [↓ ZIP](#)

3D [↓ ZIP](#)



Schematic light drawing



Beam Angle: 53°

h(m)	E(lx)	D(m)
1	1030	1.00
2	258	2.00
3	114	3.00
4	64	4.00
5	41	5.01

Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	3000
CRI>	90
Beam angle C0-180 (°)	53
Beam angle C90-270 (°)	54

Electrical

Insulation class	I
Frequency (Hz)	50/60
Main voltage (Vac)	18.20
Driver	Integrated
Dimmable	No
Dimming type	Non Dimmable
Emergency type	No