



# **Arrangements Drop Up**

Designed by Michael Anastassiades, 2018

32W - 1530lm - 2700K

Diffuse light suspended lighting device. Body in extruded, curved NC-machined and black powder-coated aluminium, diffuser in platinum optical silicone. Each component can be connected to the power pack by means of an electrical and mechanical connection system designed for customisable product set-up. Roses available with two powers: lamp with power under 70W and lamp with power under 190W. Class III roses also available for installations with remote power supply: "surface" version for installations on cement, "recessed" version for plasterboard ceilings. The electronics integrated in the rose enables use of dimming systems: push, 1-10, potentiometer, DALI. In the absence of these systems, the light flow can be set with the push system included in the rose. Cable length 2.4m



Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT

## Main specifications

EAN	8059607014165
Mounting	Suspension
Environments	Indoor dry location
Light Source Type	LED
LED type	LED Module
Power (W)	32
System flux (lm)	1530

## **Physical**

Colour	Black
Length (mm)	495
Cord length (mm)	2500
Net weight (kg)	0.65
Package height (mm)	45
Package width (mm)	545
Package length (mm)	755
Package volume (m3)	0.02
IP internal	20

#### Download

Mounting instructions	$\overline{\mathbf{A}}$	PDF
Snare Parts	$\downarrow$	PDF

# Photometric Files

LDT / IES



## **Technical Drawings**

2D	<u>↓</u> ZIP
3D	<b>⊥</b> ZIP
<b>⋒</b> Bim	<b>⊥</b> ZIP



















https://professional.flos.com/en/global/product/arrangements-drop-up-f0414030/

F0414030

# Schematic light drawing



# **Ecodesign and Energy** Labelling

This product contains a light source of energy efficiency class F



Replaceable (LED only) light source by a professional

### Photometric

Lighting type	Indirect, Direct
Light distribution	Symmetric
CCT (K)	2700

#### Electrical

Insulation class	III
Frequency (Hz)	50/60
Main voltage (Vac)	48
LED voltage Vf (Vdc)	null
Driver	Remote
Dimmable	Yes
Dimming type	Electronic 48V
Dimming interface	Remote Dimmable (Dimmer Not Included)
Batteries inside	No

## **Accessories & Power Supply**

